

DOOR SCHEDULE

MARK	SIZE	THICK	JAMB THICK	TYPE	MATERIAL	MODEL
1	9'-0" X 7'-0"	1 3/4"	6 1/2"	DVRHD	FIBERGLASS	
2	9'-0" X 7'-0"			DVRHD	FIBERGLASS	
3	3'-0" X 6'-8"			ENTRANCE	STEEL	LHRB
4	3'-0" X 6'-8"			EXTERIOR	STEEL	RHRB
5	3'-0" X 6'-8"		6 1/2"	EXTERIOR	STEEL	RHRB
6	3'-0" X 6'-8"		4 1/2"	INTERIOR	WOOD	LHRB
7	5'-0" X 6'-8"			BI-FOLD		
8	4'-0" X 6'-8"			BI-FOLD		
9	3'-0" X 6'-8"			INTERIOR		LHRB
10	1'-6" X 6'-8"			INTERIOR		RHRB
11	2'-8" X 6'-8"			INTERIOR		LHRB
12	1'-8" X 6'-8"			INTERIOR		RHRB
13	3'-0" X 6'-8"			INTERIOR		RHRB
14	5'-0" X 6'-8"			BI-FOLD		
15	3'-0" X 6'-8"			INTERIOR		LHRB
16	2'-6" X 6'-8"		4 1/2"	INTERIOR	WOOD	RHRB
17	3'-0" X 6'-8"	1 3/4"	6 1/2"	EXTERIOR	STEEL	LHRB

NOTE: DOOR #4 TO BE FIRE RATED 45 MIN. W/ SELF CLOSER MECHANISM OR HINGES
 NOTE: DOOR FOR MECHANICAL ROOM IS TO BE FIRE RATED 45 MIN. W/ SELF CLOSER MECHANISM OR HINGES

